

# KT16 RESIDENTIAL OR COMMERCIAL CENTRE FOLD SERIES: Interior Folding Door Track & Hardware

## ARCHITECTURAL SPECS

<b>MAXIMUM DOOR WEIGHT:</b>	45 lbs (20 kg) = 1 x two wheel hanger. 90 lbs (40 Kg) = 1 x four wheel hanger.
<b>MIN &amp; MAX DOOR THICKNESS:</b>	1-3/8" (35mm) to 1-3/4" (44.45mm)
<b>MAXIMUM CAPACITY:</b>	Width and height of the door may vary beyond standard sizes provided the weight of the door does not exceed the maximum weight listed above.
<b>VERTICAL ADJUSTMENT:</b>	1/4" (6mm)
<b>TRACK:</b>	Extruded aluminum, clear or bronze anodized. 8 stock lengths available, refer to price list.
<b>HANGER:</b>	Steel carrier, plated, 4 nylon wheels, ball bearing or Stainless steel carrier, 4 nylon wheels, ball bearing.
<b>OPTIONS:</b>	Hinges available in either brushed stainless steel or PVD bronze finish over stainless. Flushbolts available in either brushed aluminum or bronze powder coat over aluminum. KT23 extruded aluminum floor channel, bronze anodized, with PVC channel insert. 7 stock lengths available, refer to price list.

## Panel configuration examples (an odd number of panels is required to swing a service door)

FB = Flushbolt may be installed top or bottom, or both.

