


# KT15 COMMERCIAL SERIES: Bifold Door Track & Hardware

## ARCHITECTURAL SPECS

<b>MAXIMUM DOOR WEIGHT:</b>	120 lbs (55 kg) per bi-fold door (2 leaves)	 2 leaves= 1 door
<b>MIN &amp; MAX DOOR THICKNESS:</b>	3/4" (19mm) to 1-3/4" (44.45mm)	
<b>MAXIMUM CAPACITY:</b>	Max leaf width = 24" (609mm). Max door height = 96" (2834mm). For door leaves over 18" (457mm) wide and or over 33 lbs (15 kg) in weight, bottom guiding system must be used.	
<b>VERTICAL ADJUSTMENT:</b>	1/4" (6mm)	
<b>TRACK:</b>	Extruded aluminum, mill finish. 7 stock lengths available, refer to price list.	
<b>HANGER / PIVOTS:</b>	Steel carrier, plated, 4 nylon wheels, ball bearing. Pivots are steel and nylon.	
<b>OPTIONS:</b>	KT20 extruded aluminum floor channel, with KT120 steel plate, nylon swivel guide	
<b>HARDWARE KITS:</b>	KT15KIT-2L for 2 leaf application, consists of KT15HANGER (1 ea), KT15PIVOT (1 ea) top and bottom pivots, KT189 (1 ea) knob, KT157 (1 ea) wrench, installation sheet plus all screws.	
<b>NOTE:</b>	For multiple leaves folding to one side use one KT15KIT-2L for the first 2 leaves and for each additional 2 leaves add one KT15HANGER & one KT189 bifold door knob.	

