

KT1080 RESIDENTIAL SERIES: Pocket in a Box - Light Duty Economy Model

KT25TRACK with Axle Wheels - Max door weight: 100 lbs (45 kg)

Knock Down Pocket Door Frame with Track And Hardware Kit.

For 4-1/2" (114.3mm) Wall

ARCHITECTURAL SPECS

ROUGH OPENING (RO)	The width is calculated by multiplying the door width by two and adding 1" (25.4mm) IE: 36" x 2 = 72"; 72" + 1" = 73" opening Rough opening in height is 4" more than door height. (914 x 2 = 1828; 1828 + 25.4 = 1853mm)
MAX DOOR WEIGHT	100 lbs (45 kg)
MIN AND MAX DOOR THICKNESS	3/4" (19mm) to 1-3/8" (35mm)
VERTICAL ADJUSTMENT	3/8" (9.5mm)
DOOR WIDTH & HEIGHT	Width: 24" (609mm) to 36" (914mm) / Height: Up to 80" (2032mm)
TRACK	Extruded aluminum, keyhole punched
HANGER	Steel construction zinc plated, 4 plastic wheels
HARDWARE PACKS	Included in box for 1 door application. Consists of (poly-bagged) KT25 HANGER-2 hangers, KT107-1 jamb mounted door guide, KT122-1 nail on bumper stop, KT155-1 wrench, KT143-2 bottom jamb spacer plates, KT144 -2 brackets for KD pocket door frame header, installation sheet plus all screws

NOTE: After installing pocket frames, replace all track screws with #8 x 11/2" (38mm) screws (included), before drywall.

