

KT1400 COMMERCIAL SERIES: Pocket in a Box - Heavy Duty Model

KT40TRACK with Ball Bearing Wheels - Max door weight: 220 lbs (100 kg)

Knock Down Pocket Door Frame with Track And Hardware Kit, For 4-1/2" (114.3mm) Wall.

For 6-1/2" (165mm) Wall • KT1410 also available for max door weight of 220 lbs (100 kg) using KT40TRACK and KT40HANGER with ball bearing wheels

ARCHITECTURAL SPECS

ROUGH OPENING (RO)	The width is calculated by multiplying the door width by two and adding 1" (25.4mm) IE: 36" x 2 = 72"; 72" + 1" = 73" opening. Rough opening in height is 4" more than door height. (914 x 2 = 1828; 1828 + 25.4 = 1853mm)
MAX DOOR WEIGHT	KT1400 Series: 220 lbs (100kg), 2 hangers, for 4-1/2" (114.3mm) wall (Standard) KT1410 Series: 220 lbs (100kg), 2 hangers, for 6-1/2" (165mm) wall
MIN AND MAX DOOR THICKNESS	3/4" (19mm) to 1-3/8" (34.9mm). Up to 2" (51mm) with modification to header
VERTICAL ADJUSTMENT	KT1400: 3/4" (19mm)
DOOR WIDTH & HEIGHT	Width: 24" (609mm) to 48" (1219mm) Height: Up to 108" (2743mm) provided door does not exceed 220 lbs (100 kg)
TRACK	KT40 extruded aluminum, punched
HANGER	Steel construction zinc plated, 4 nylon wheels ball bearing
HARDWARE PACKS	Included in box for 1 door application. Consists of (poly-bagged) KT40HANGER-2 hangers, KT107-1 jamb mounted door guide, KT122-1 nail on bumper stop, KT157-1 wrench, KT143-2 bottom jamb spacer plates, KT144 -2 brackets for KD pocket door frame header, installation sheet plus all screws

NOTE: After installing pocket frames, replace all track screws with #8 x 1 1/2" (38mm) screws (included), before drywall.

